

# CentOS Stream 8 – Jetty 10

Version:	1.0.0
Created by:	cloudimg

## Table of Contents

1.) Overview.....	1
2.) Access & Security.....	1
3.) System Requirements.....	2
4.) Connecting to the Instance.....	2
5.) On Startup.....	2
6.) Filesystem Configuration.....	3
7.) Server Components.....	3
8.) Scripts and Log Files.....	4
9.) Using System Components.....	4

## 1.) Overview

This document is provided as a user guide for the CentOS Stream 8 – Jetty 10 product offering on the Azure Marketplace. Please reach out to [support@cloudimg.co.uk](mailto:support@cloudimg.co.uk) if any issues are encountered following this user guide for the chosen product offering.

## 2.) Access & Security



Registered  
Technology  
Partner

cloudimg  
(+44) 02045382725  
3rd Floor 86-90 Paul Street London EC2A 4NE  
[support@cloudimg.co.uk](mailto:support@cloudimg.co.uk)  
<https://cloudimg.co.uk>

Please update the security group of the target instance to allow the below ports and protocols for access and connectivity.

Protocol	Type	Port	Description
SSH	TCP	22	SSH connectivity
HTTP	TCP	8080	Jetty Front End

### 3.) System Requirements

The minimum system requirements for the chosen product offering can be found below

Minimum CPU	Minimum RAM	Required Disk Space
1	1 GB	20 GB

### 4.) Connecting to the Instance

Once launched in the Azure Virtual Machines Service, please connect to the instance via an SSH client using the **azureuser** with the key pair associated at launch. Once connected as the **azureuser**, you will be able to **sudo** to the **root** user by issuing the below command.

Switch to the root user

```
sudo su -
```

### 5.) On Startup

An OS package update script has been configured to run on boot to ensure the image is fully up to date at first use. You can disable this feature by removing the script from `/stage/scripts/` and deleting the entry in crontab for the root user.

Disable the OS update script from running on reboot

```
rm -f /stage/scripts/initial_boot_update.sh  
crontab -e  
#DELETE THE BELOW LINE. SAVE AND EXIT THE FILE.  
@reboot /stage/scripts/initial_boot_update.sh
```



Registered  
Technology  
Partner

cloudimg  
(+44) 02045382725  
3rd Floor 86-90 Paul Street London EC2A 4NE  
support@cloudimg.co.uk  
<https://cloudimg.co.uk>

## 6.) Filesystem Configuration

Please see below for a screenshot of the server disk configuration and specific mount point mappings for software locations.

```
Filesystem      Size  Used Avail Use% Mounted on
devtmpfs        1.9G   0  1.9G   0% /dev
tmpfs           2.0G   0  2.0G   0% /dev/shm
tmpfs           2.0G  8.5M  1.9G   1% /run
tmpfs           2.0G   0  2.0G   0% /sys/fs/cgroup
/dev/nvme0n1p2  38G  2.5G  33G   7% /
/dev/nvme0n1p1  2.0G 121M  1.7G   7% /boot
tmpfs           391M   0  391M   0% /run/user/1002
/dev/nvme1n1    9.8G 308M  9.0G   4% /apps
```

Mount Point	Description
/boot	Operating System Kernel files
/apps	Java & Jetty installation directory

## 7.) Server Components

Please see below for a list of installed server components and their respective installation paths. The below versions are subject to change on initial boot based on the initial\_boot\_update.sh script finding new versions of the software in the systems package repositories.

Component	Version	Software Home
Cloud-Init	22.1	/etc/cloud
Java	11	/apps/java
Jetty	10.0.13	/apps/jetty
Azure CLI	2.53.1	/lib64/az



Registered  
Technology  
Partner

cloudimg  
(+44) 02045382725  
3rd Floor 86-90 Paul Street London EC2A 4NE  
support@cloudimg.co.uk  
<https://cloudimg.co.uk>

## 8.) Scripts and Log Files

The below table provides a breakdown of any scripts & log files created to enhance the useability of the chosen offering.

Script/Log	Path	Description
Initial_boot_update.sh	/stage/scripts	Update the Operating System with the latest updates available.
Initial_boot_update.log	/stage/scripts	Provides output for initial_boot_update.sh

## 9.) Using System Components

Instructions can be found below for using each component of the server build mentioned in section 7 of this user guide document.

### Azure CLI

Using Azure CLI - as any OS user.

```
az
```

### Cloud-Init

Edit the /etc/cloud/cloud.cfg file to reflect your desired configuration. A link to the cloud-init official documentation can be found below for referencing best practise for your use case.

<https://cloudinit.readthedocs.io/en/latest/>

```
vi /etc/cloud/cloud.cfg
```

### Java

Java has been preinstalled on the instance and the below command can be used to verify the version currently installed.



Registered  
Technology  
Partner

cloudimg  
(+44) 02045382725  
3rd Floor 86-90 Paul Street London EC2A 4NE  
support@cloudimg.co.uk  
<https://cloudimg.co.uk>

```
java -version
```

## Jetty

Start and Stop scripts have been created under the home directory of the jetty user. Issue the below commands to start and or stop the Jetty service as the jetty user.

```
#Switch to the jetty OS user

sudo su - jetty

#Start the Jetty service

$HOME/jetty-start.sh

#Stop the Jetty service

$HOME/jetty-stop.sh

#Check the status of the Jetty service

$HOME/jetty-status.sh
```


Once the Jetty service has started, you will be able to access the Jetty front end via the below URL exchanging the values between <> to match that of your own instance.

<PRIVATE/PUBLICIP>:8080



Registered  
Technology  
Partner

cloudimg  
(+44) 02045382725  
3rd Floor 86-90 Paul Street London EC2A 4NE  
support@cloudimg.co.uk  
<https://cloudimg.co.uk>



## Welcome to Jetty 10

The Jetty project is a 100% Java [Servlet](#) Container which supports asynchronous server and client implementations of the HTTP, WebSocket and HTTP/2 protocols. The project is 100% Open Source and hosted by the Eclipse Foundation at <https://www.eclipse.org/jetty/>.

demos	information	getting help
<ul style="list-style-type: none"><li>• <a href="#">Demo Jetty Webapp</a></li><li>• <a href="#">Servlet 4.0 Test</a></li><li>• <a href="#">JSP Demos</a></li><li>• <a href="#">JAAS Demo</a></li><li>• <a href="#">JNDI Demo</a></li><li>• <a href="#">Async Rest Demo</a></li><li>• <a href="#">Redirected Context</a></li></ul>	<ul style="list-style-type: none"><li>• <a href="#">Jetty Homepage</a></li><li>• <a href="#">Jetty Documentation Hub</a></li><li>• <a href="#">Javadoc (via transparent proxy)</a></li><li>• <a href="#">Jetty Powered</a></li><li>• <a href="#">Optional content found only in 'jetty-home-cvezp-with-docs.zip'</a><ul style="list-style-type: none"><li>◦ <a href="#">Jetty Documentation</a></li><li>◦ <a href="#">Javadoc</a></li></ul></li></ul>	<ul style="list-style-type: none"><li>• <a href="#">Mailing lists @ eclipse</a></li><li>• <a href="#">Source @ github</a></li><li>• <a href="#">Developer Advice</a></li><li>• <a href="#">Custom Development</a></li><li>• <a href="#">Production support</a></li><li>• <a href="#">Jetty @ Stackoverflow</a></li><li>• <a href="#">Embedded Jetty @ Stackoverflow</a></li></ul>

## Jetty Developer's Blog

---



Registered  
Technology  
Partner

cloudimg  
(+44) 02045382725  
3rd Floor 86-90 Paul Street London EC2A 4NE  
[support@cloudimg.co.uk](mailto:support@cloudimg.co.uk)  
<https://cloudimg.co.uk>