

# CentOS Stream 8 – Redis

Version:	1.0.0
Created by:	cloudimg

## Table of Contents

1.) Overview.....	1
2.) Access & Security.....	1
3.) System Requirements.....	2
4.) Connecting to the Instance.....	2
5.) On Startup.....	2
6.) Filesystem Configuration.....	3
7.) Server Components.....	3
8.) Scripts and Log Files.....	4
9.) Using System Components.....	4

## 1.) Overview

This document is provided as a user guide for the CentOS Stream 8 – Redis product offering on the Azure Marketplace. Please reach out to [support@cloudimg.co.uk](mailto:support@cloudimg.co.uk) if any issues are encountered following this user guide for the chosen product offering.

## 2.) Access & Security



Registered  
Technology  
Partner

cloudimg  
(+44) 02045382725  
3rd Floor 86-90 Paul Street London EC2A 4NE  
[support@cloudimg.co.uk](mailto:support@cloudimg.co.uk)  
<https://cloudimg.co.uk>

Please update the security group of the target instance to allow the below ports and protocols for access and connectivity.

Protocol	Type	Port	Description
SSH	TCP	22	SSH connectivity
Custom TCP	TCP	6379	Redis database listener port

### 3.) System Requirements

The minimum system requirements for the chosen product offering can be found below

Minimum CPU	Minimum RAM	Required Disk Space
1	1 GB	20 GB

### 4.) Connecting to the Instance

Once launched in the Azure Virtual Machines Service, please connect to the instance via an SSH client using the **azureuser** with the key pair associated at launch. Once connected as the **azureuser**, you will be able to **sudo** to the **root** user by issuing the below command.

Switch to the root user

```
sudo su -
```

### 5.) On Startup

An OS package update script has been configured to run on boot to ensure the image is fully up to date at first use. You can disable this feature by removing the script from `/stage/scripts/` and deleting the entry in crontab for the root user.

Disable the OS update script from running on reboot

```
rm -f /stage/scripts/initial_boot_update.sh  
crontab -e  
#DELETE THE BELOW LINE. SAVE AND EXIT THE FILE.  
@reboot /stage/scripts/initial_boot_update.sh
```



Registered  
Technology  
Partner

cloudimg  
(+44) 02045382725  
3rd Floor 86-90 Paul Street London EC2A 4NE  
support@cloudimg.co.uk  
<https://cloudimg.co.uk>

## 6.) Filesystem Configuration

Please see below for a screenshot of the server disk configuration and specific mount point mappings for software locations.

```
Filesystem      Size  Used Avail Use% Mounted on
devtmpfs        464M   0  464M   0% /dev
tmpfs           481M   0  481M   0% /dev/shm
tmpfs           481M  6.5M  475M   2% /run
tmpfs           481M   0  481M   0% /sys/fs/cgroup
/dev/xvda2       38G   2.8G   33G   8% /
/dev/xvda1      2.0G  185M  1.7G  11% /boot
tmpfs            97M   0   97M   0% /run/user/1002
/dev/xvdf        9.8G   37M   9.3G   1% /var/lib/redis
```

Mount Point	Description
/boot	Operating System Kernel files
/var/lib/redis	Redis data directory

## 7.) Server Components

Please see below for a list of installed server components and their respective installation paths. The below versions are subject to change on initial boot based on the initial\_boot\_update.sh script finding new versions of the software in the systems package repositories.

Component	Version	Software Home
Cloud-Init	22.1	/etc/cloud
Redis	6.2.7	/etc/redis.conf
Azure CLI	2.53.1	/lib64/az



Registered  
Technology  
Partner

cloudimg  
(+44) 02045382725  
3rd Floor 86-90 Paul Street London EC2A 4NE  
support@cloudimg.co.uk  
<https://cloudimg.co.uk>

## 8.) Scripts and Log Files

The below table provides a breakdown of any scripts & log files created to enhance the useability of the chosen offering.

Script/Log	Path	Description
Initial_boot_update.sh	/stage/scripts	Update the Operating System with the latest updates available.
Initial_boot_update.log	/stage/scripts	Provides output for initial_boot_update.sh
redis_secure_password.log	/stage/scripts	Redis secure database password log file

## 9.) Using System Components

Instructions can be found below for using each component of the server build mentioned in section 7 of this user guide document.

### Azure CLI

Using Azure CLI – as any OS user.

```
az
```

### Cloud-Init

Edit the /etc/cloud/cloud.cfg file to reflect your desired configuration. A link to the cloud-init official documentation can be found below for referencing best practise for your use case.

<https://cloudinit.readthedocs.io/en/latest/>

```
vi /etc/cloud/cloud.cfg
```

### Redis

The Redis database service has been configured to start on boot, please use the below commands to start, stop and check the status of the service.



Registered  
Technology  
Partner

cloudimg  
(+44) 02045382725  
3rd Floor 86-90 Paul Street London EC2A 4NE  
support@cloudimg.co.uk  
<https://cloudimg.co.uk>

```
#Check the Redis Server is running
systemctl status redis

#Stop the Redis Server
systemctl stop redis

#Start the Redis Server
systemctl start redis
```

Once the redis server status has started, you will be able to access database command line interface by following the instructions in the log file `/stage/scripts/redis_secure_password.log`

#### EXAMPLE LOG FILE

```
cat /stage/scripts/redis_secure_password.log
```

```
Redis secure password: lsddfsQcVrF4kOJCvPdasHlvNs0I+sdafwR6BPXJ+Xidf9TGvy4KddXali0=
```

```
Access Redis as root user using the command: redis-cli
```

```
At the 127.0.0.1:6379> prompt, enter AUTH followed by the password shown above for authentication, example: AUTH lsddfsQcVrF4kOJCvPdasHlvNs0I+sdafwR6BPXJ+Xidf9TGvy4KddXali0=
```

```
You will receive an OK message upon successful connection
```



Registered  
Technology  
Partner

cloudimg  
(+44) 02045382725  
3rd Floor 86-90 Paul Street London EC2A 4NE  
support@cloudimg.co.uk  
<https://cloudimg.co.uk>